



## El Mar® Mid Ash Supreme GEO

Phillips 66® El Mar Mid Ash Supreme GEO is a premium quality, mid-ash, dispersant-detergent gas engine oil designed for use in naturally aspirated and moderately to highly turbocharged 4-stroke cycle natural gas engines. It is particularly recommended for use in natural gas engines and dual-fuel engines burning sour gas or landfill gas.

El Mar Mid Ash Supreme GEO is formulated with field-proven performance additives to provide excellent resistance to oxidation and nitration, protect against piston scuffing and wear, and minimize the formation of sludge and piston deposits for good engine cleanliness. It has a high alkaline reserve (TBN) to protect engines operating under corrosive conditions, such as when burning sour gas, digester gas or landfill gas.

El Mar Mid Ash Supreme GEO is recommended for use in other 4-stroke cycle natural gas engines that require a mid-ash gas engine oil containing 1% (nominal) sulfated ash.

### Applications

- 4-stroke cycle gas and dual-fuel engines burning sour gas or landfill gas
- 4-stroke cycle gas engines in wastewater treatment plants fueled by digester gas
- 4-stroke cycle converted irrigation engines running on natural gas or LPG
- Other 4-stroke cycle natural gas engines where the manufacturer specifies a mid-ash gas engine oil

El Mar Mid Ash Supreme GEO is recommended for use in natural gas engines manufactured by:

- Colt-Fairbanks Morse
- Cooper Superior
- Nordberg
- Waukesha

## Premium Mid-Ash Natural Gas Engine Oil





## Features/Benefits

- Field-proven performance in providing outstanding engine cleanliness
- Proven performance in lean-burn engines
- High dispersancy protects against engine sludge and varnish deposits
- Excellent resistance to oil oxidation and nitration
- Protects against scuffing and wear
- Protects against rust and corrosion
- Protects against valve stem deposits and valve recession
- Compatible with emissions system catalysts
- Does not contain any bright stock, which can cause harmful carbon deposits

## El Mar<sup>®</sup> Mid Ash Supreme GEO

Typical Properties			
SAE Grade	30	40	15W-40
Specific Gravity @ 60°F	0.886	0.894	0.875
Density, lbs/gal @ 60°F	7.38	7.45	7.29
Color, ASTM D1500	8.0	8.0	8.0
Flash Point (COC), °C (°F)	216 (421)	225 (437)	232 (450)
Pour Point, °C (°F)	-33 (-27)	-24 (-11)	-39 (-38)
Viscosity, Kinematic			
cSt @ 40°C	91.0	146	102
cSt @ 100°C	10.9	14.4	14.1
Viscosity Index	104	96	141
Cold Cranking Viscosity, cP @ (°C)	---	---	5800 (-20)
Sulfated Ash, ASTM D874, wt %	1.0	1.0	1.0
Total Base Number (TBN), ASTM D2896	8.2	8.2	8.2
Phosphorus, wt %	0.028	0.028	0.028
Zinc, wt %	0.032	0.032	0.032

## Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.

09-13-2016

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© Phillips 66 Company. Phillips 66<sup>®</sup> and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.